



9	44	DIN EN ISO 4014 - M16 x 55 - 10.9	-	Sechskantschraube - M16 x 55 - 10.9	-	-	-
8	88	DIN 6796	-	Spannscheibe DIN 6796 16	-	-	-
7	44	DIN EN 24032 M16-10	-	Sechskantmuttern M16-10	-	-	-
6	22	SE 316-05	-	WELDED-GROUP	-	-	-
5	2	SE 316-11	-	RESCUE-DEVICE	-	-	-
4	4	SE 316-07	-	SQUARING BEAM	-	-	-
3	7	SE 316-05	-	CROSS-BEAM	-	-	-
2	2	SE 316-01	-	LONGITUDINAL BEAM	-	-	-
1	2	1.0570	01 01 001	DISTANZPLATTE	90 x 65 x 25	1100 g	-
POS	STCK	TEILESTAMMDATEN	PART-NAME	BENENNUNG	ABMASSE	MASSE	BEMERKUNG

SURFACE FINISH DIN ISO 1302		AFFECTATION A/C PART NBR		SCALE 1:20 (1:5)	
EDGES DIN 6784-D2		A/C DRWG NBR		GENERAL TOLERANCES DIN ISO 2768-m-K	
PLANT DEPARTMENT	HAMBURG TMDAAJ1	SHEET	ISSUE	FIRST ANGLE PROJECTION	SIZE A0
DRN	D. Albu	CHKD		TITLE	A00
DATE	22-May-12	DATE		UNTERRAHMEN VORN	ISSUE
MANUF. CODE	D0181	APPD		SHEET 01 OF 01 SHEETS	
COMPUTER PRODUCED DRAWING USING CATIA V5... NO MANUAL ALTERATION					

BEI POS.6, POS.7, POS.8 UND POS.9 BESCHICHTUNG MIT "DACROMET 500".
 ANZUGSMOMENT 200Nm.

