



# CEME S.p.A.

## fluid control components

[Italiano](#) [English](#)

CERCA >

- [COMPANY](#)
- [PRODUCTS](#)
- [SITE MAP](#)
- [CONTACTS](#)

Pumps Water

## Series ET30..

SOLENOID PUMP

ELECTRICAL CONNECTION

- (A.C. ~) through a diode
- (D.C. =) requires the use of a square waves impulse converter
- supplied with THREE POLE PLUG CONNECTOR UNI ISO 4400 (DIN 43650A)
- IP 65 with included diode.

COIL

- polybutylene terephthalate (PBT)
  - insulation class: I
  - thermic class: H (180°C)
- The coil is provided with a pocket for the thermoswitch in series connected to the line terminal to prevent



MOUNTING POSITION	overheating of the coil in any position, preferable the horizontal one
TUBE GUIDE	stainless steel
PISTON AND SPRING	stainless steel high corrosion resistance
SEALINGS	FKM, H-NBR
SLIDING GUIDE	PTFE, FKM (3000)
AMBIENT TEMPERATURE	50°C (3000), 70°C (3009)
FLUID TEMPERATURE	25°C (3000), 60°C (3009)
FLUIDS	water and non corrosive media
SUCTION PREVALENCE	1 m
TOLERANCE	all the performances apply within a tolerance of ± 15%
SPECIAL EXECUTIONS	VOLTAGE 120V 60 HZ
ACCESSORIES	SEE CHAPTER ACCESSORIES

 **INDUSTRIAL DIVISION**



- [APPLIANCES DIVISION](#)
- [INDUSTRIAL DIVISION](#)
- [Air](#)
- [Water](#)
- [-Solenoid Valves](#)

- [-Pumps](#)
- [-Press. switches](#)
- [-Flow Control](#)
- [-Level Regulator](#)
- [Innert Gas](#)
- [Gas](#)
- [Steam](#)
- [Refrigerants](#)
- [COFFEE DIVISION](#)
- 
- [TECHNICAL INFORMATION](#)
- [CATALOGUES](#)
- 
- 

**CEME S.p.A.** Via del Lavoro, 2 - 20061 Carugate (MI) Italy - Tel. +39  
02921562.1 - Fax. +39 0292150083 - P.IVA/C.F. 06259720966 - R.I.  
1880055 MI